FILAKRISTALL PLUS

PROFESSIONAL CRYSTALLIZER





- POLISHED MARBLE
- POLISHED
 - **AGGLOMERATES**
- NATURAL STONES POLISHED LIMESTONE



WHAT IT'S FOR

- Professional product which restores sheen to worn surfaces.
- Ideal for crystallizing natural polished limestone (marble, travertine) and polished agglomerates.

ADVANTAGES

- Rapidly restores the natural sheen to materials.
- Easy to apply and maintain.
- Keeps the surface shiny while making it resistant to wear.
- Anti-slip polishing.
- Increases traffic resistance.
- Worn material easily and quickly regains over 90% of its original shine (mean value obtained with lab testing).

COVERAGE

With one litre:

50 m²

"Coverage shown is for guidance purposes only and refers to single coats"

HOW TO USE IT

No dilution required: ready to use.

Application: Shake well before use and apply using a spray. To ensure perfect crystallization, clean the floor and remove any wax residues before applying.

- 1. Wash the floor with FILAPS87 dewaxing. degreasing detergent. Rinse thoroughly and leave
- 2. Once the surface clean and dry, spray a small amount of FILAKRISTALL PLUS over a limited area (around 2 sq.m). Immediately work the product evenly **over the surface using a single-disc machine fitted with a white disc** (recommended speed 150 rpm). As soon as the disc encounters resistance, replace it with a stainless steel wool disc and continue for a few minutes until the polished effect is achieved (recommended speed 400 rpm). Repeat the procedure for the rest of the surface to
- 3. Remove the steel wool fibres by wiping the surface with a microfibre or soft cotton cloth.
- 4. Repeat the above procedures until you reach the required level of sheen.
- 5. When completed, dry-polish using a single-disc machine fitted with a soft white microfibre disc or a white disc and a dusting cloth.

Caution: Avoid leaving water to stand on the floor or allowing the product to drip from the container. Do not use on non-limestone surfaces such as granite, quartzite or sandstone in general. Avoid contact with materials such as wood, terracotta,

ceramic and metal (edges in steel and aluminium). Carry out a spot test beforehand to check the effect

of the treatment

Appearance: liquid Colour: cream/hazelnut Odour: characteristic

Density: 1.09 kg/l

Solubility: soluble in water

This information is the result of our most up-to-date technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring. Fila shall not accept any responsibility for improper use of its products.

Packaging

1-litre cans in boxes of 6.

WARNINGS

- Acidic product
- Use protective goggles and rubber gloves.
 Separation of the product in no way compromises
- Avoid contact with eyes and skin.
 Product in emulsion. Do not freeze.

TEMPERATURES

Storage temperature: 10° to 30°C
The product must be applied to material with a temperature between 10° and 30°C.

COMPOSITION

Water-based emulsion of natural and synthetic waxes, non-ionic surfactants, polymer suspension, inorganic acid.

LABELLING Signal words: Warning

Harmful if swallowed. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Avoid release into the environment. Wear protective gloves/ protective clothing/eye protection/face protection. IF SWALLOWED: Call a POISON CENTER or doctor / physician if you feel unwell. Dispose of contents / container in accordance with official regulations Contains: ESAFLUOROSILICATO DI MAGNESIO **TECHNICAL FEATURES**